

# LIGHTNING EVENT COUNTER WITH REMOTE MONITORING



## FEATURES

Installs on downconductor to record number of lightning strikes

Fibre optic output allows remote monitoring of the lightning activity

For use with nVent ERICO Ericore, conventional conductors or tape

## SPECIFICATIONS

Table 1/2

Catalog Number	Trip Threshold	Depth (D)	Height (H)	Width (W)	Temperature	Cable Length
LECIVR	2	65mm	110 mm	80 mm	-40 to 50 °C	25m

Table 2/2

Catalog Number	Unit Weight
LECIVR	0.52 kg

## DIAGRAMS



**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

**Europe**

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

**Europe**

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

**APAC**

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**