

DIGITAL LIGHTNING EVENT COUNTER



FEATURES

Records quantity, hour and date of lightning strikes for retrieval during inspections

Includes mounting brackets for use with nVent ERICO Ericore, ISOnV, bare stranded conductors or tape


Includes replaceable CR17335 lithium 3V battery

Up to five year battery life

SPECIFICATIONS

Table 1/2							
Catalog Number	Material	Enclosure Rating	Trip Threshold	Depth (D)	Height (H)	Width (W)	
LECV	Polycarbonate	IP 65, NEMA®-4	1 - 100 kA 8/20 μs	42mm	141 mm	91 mm	

Table 2/2							
Catalog Number	Temperature	Unit Weight	Complies With				
LECV	-40 to 80 °C	0.36 kg	EN IEC 62561-6				



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

nVent.com TRACER

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

HOFFMAN

APAC

RAYCHEM

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500

SCHROFF



© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

CADDY ERICO

nVent reserves the right to change specifications without notice.