


NVENT ERICO CADWELD EXOLON, BUSBAR TO BUSBAR



Developed in 1988, nVent ERICO Cadweld Exolon connections represented a significant advancement in welded electrical connections for sensitive indoor applications like data centers, hospitals, and other clean room environments. The virtual elimination of smoke and a unique electronic starting system makes this an ideal solution for sensitive applications. Each nVent ERICO Cadweld Exolon package contains ceramic filters that produce an extremely low emission connection.

CERTIFICATIONS





FEATURES

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

SPECIFICATIONS

| Table 1/2 | | | | | | |
|-------------------|----------------|--------------------|----------------------|-----------|----------------------|----------------------------|
| Catalog Number | Mold Family | Baffle Assembly | Lug/Busbar Size 2 | Price Key | Lug/Busbar Size 1 | Handle Clamp |
| XLBACCAJ | BA Mold Family | | 3 mm x 25 mm | XLC | 3 mm x 25 mm | XLL160, Sold Separately |
| XLBFDCAJPAM | BF Mold Family | | 6 mm x 50 mm | XLD | 3 mm x 25 mm | XLL159, Sold Separately |

| Catalog Number | Mold Family | Baffle Assembly | Lug/Busbar Size 2 | Price Key | Lug/Busbar Size 1 | Handle Clamp |
|-------------------|----------------|------------------------------|----------------------|-----------|----------------------|----------------------------|
| XLBFDCAJPAM S | BF Mold Family | XLB973A1, Sold Separately | 6 mm x 50 mm | XLD | 3 mm x 25 mm | XLL159, Sold Separately |
| XLBQCCAJCAJ | BQ Mold Family | | 3 mm x 25 mm | XLC | 3 mm x 25 mm | XLL160, Sold Separately |
| XLBQCCAJPAM | BQ Mold Family | | 6 mm x 50 mm | XLC | 3 mm x 25 mm | XLL160, Sold Separately |
| XLBQCCAJPAM S | BQ Mold Family | XLB972A1, Sold Separately | 6 mm x 50 mm | XLC | 3 mm x 25 mm | XLL160, Sold Separately |

| Table 2/2 | | | | |
|----------------|------------------------|----------------|--|--|
| Catalog Number | Welding Material | Certifications | | |
| XLBACCAJ | XL65, Sold Separately | cUL, UL | | |
| XLBFDCAJPAM | XL400, Sold Separately | | | |
| XLBFDCAJPAMS | XL400, Sold Separately | | | |
| XLBQCCAJCAJ | XL90, Sold Separately | | | |
| XLBQCCAJPAM | XL200, Sold Separately | | | |
| XLBQCCAJPAMS | XL200, Sold Separately | | | |

ADDITIONAL PRODUCT DETAILS

A gap between conductors may be required. See mold tag for more information.

| XL-XX-X-XX-L-M-W | | | | |
|------------------|----------------------------------|-----------------------------------------------------------------------------------------|--|--|
| XL | ERICO CADWELD EXOLON Designation | | | |
| XX | Mold Family | | | |
| Χ | Price Key | | | |
| XX | Lug/Busbar Size 1 | | | |
| XX | Lug/Busbar Size 2 | | | |
| L* | Split Crucible | Crucible section is split on molds designed with horizontal opening for easier cleaning | | |
| M* | Mold Only | | | |
| W* | Wear Plates | Reduce mechanical abrasion of molds at cable entry points | | |

^{*} Empty if none

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.