

## PROLINE FRONT-TO-BACK D-RING BRACKET



The Front-to-Back D-Ring Bracket manages cable routed between the front and back of a cabinet. It can be used with optional Universal D-Ring Brackets or Transition Brackets for increased flexibility in managing cables. The bracket mounts to any ProLine frame. It secures cable with D-Rings that snap open and closed for secure routing with easy access for wiring changes. The D-Rings can be oriented for vertical, front-to-back or side-to-side cable management. Please note this kit includes D-Rings and mounting hardware.

## **FEATURES**

The Front-to-Back D-Ring Bracket manages cable routed between the front and back of a cabinet

It can be used with optional Universal D-Ring Brackets or Transition Brackets for increased flexibility in managing cables

The bracket mounts to any ProLine frame

It secures cable with D-Rings that snap open and closed for secure routing with easy access for wiring changes

The D-Rings can be oriented for vertical, front-to-back or side-to-side cable management

Kit includes D-Rings and mounting hardware

## SPECIFICATIONS

Color:	Jet Black		
Material:	Mild Steel		
Finish:	Powder Coated		
Color Code:	RAL 9005		

Table 1/1				
Catalog Number	Article Number	D-Ring Quantity	Fits Enclosure Depth	Thickness
PFBDR10	16013	4	1000mm	1.9mm
PFBDR11	16014	5	1100mm	1.9mm
PFBDR12	16015	5	1200mm	1.9mm
PFBDR8	16011	3	800mm	1.9mm
PFBDR9	16012	3	900mm	1.9mm

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.