

CROSS FEED-THROUGH



Feed-Through Crosses are used for routing wires and cables in four directions. Connects to other wireway sections and fittings and protects wires and cables against dust in a broad range of industrial applications.

INDUSTRY STANDARDS

Certified by Canadian Standards Association.

FEATURES

Feed-Through Crosses are used for routing wires and cables in four directions

Connects to other wireway sections and fittings and protects wires and cables against dust in a broad range of industrial applications

SPECIFICATIONS

ANSI 61 **Color Code:** Color: Gray Material: Mild Steel Finish: Powder Coated

| Table 1/1 | | | | | | |
|-------------------|----------------|---------------|--------|-------|-----------|------------|
| Catalog Number | Article Number | Туре | Height | Width | Thickness | Quick Ship |
| F22WC | 14090 | Cross Fitting | 64mm | 64mm | 1.9mm | No |
| F44WC | 14280 | Cross Fitting | 102mm | 102mm | 1.9mm | No |
| F66WC | 14490 | Cross Fitting | 152mm | 152mm | 1.9mm | No |
| F88WC | 14700 | Cross Fitting | 203mm | 203mm | 1.9mm | No |

ADDITIONAL PRODUCT DETAILS

All dimensions are to outside surfaces. Allow .12 in. (3 mm) additional for gasket at joints. Dimension K are from intersection of center lines.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



nVent.com