

# **NVENT CADDY PYRAMID ST FIXED STRUT SUPPORT**



### **CERTIFICATIONS**



### **FEATURES**

Provides superior support for pipe, conduit, cable tray and equipment

Foam bottom offers low abrasion interface for better roof membrane protection

Compatible with roof surfaces including single ply, bituminous, metal and spray foam

Provides superior load distribution, even with varying rooftop surfaces

Ready to use out of the box, saving installation time and labor

Multiple sizes and load ratings offer the ability to tailor the solution to the application

Easy to transport to the roof

Hot-dip galvanized and UV stabilized for long lasting performance

## **SPECIFICATIONS**

Static Load Safety Factor: 3:1

Finish: Hot-Dip Galvanized

Material: Polyethylene;Polypropylene;Steel

**Temperature:** -45 to 65 °C


Table 1/2									
Catalog Number	Article Number	Length 1 (L1)	Length 2 (L2)	Height (H)	Width (W)	Surface Area			
PSF6C	360463	152 mm	203 mm	122 mm	152 mm	26452mm²			
PSF10C	360464	254 mm	317.5 mm	122 mm	203 mm	59355mm²			
PSF16C	360466	406 mm	483 mm	122 mm	203 mm	91613mm²			


Table 2/2								
Catalog Number	<b>Article Number</b>	Unit Weight	Static Load (F)	Certifications				
PSF6C	360463	0.5 kg	1334N					
PSF10C	360464	1 kg	4450N	ITB				
PSF16C	360466	1.5 kg	6670N	ITB				

### ADDITIONAL PRODUCT DETAILS

Static load at 73.1 kPa (10.6 psi) roof loading. Contact project or roofing engineer for maximum allowable load on individual project roof system.

### **DIAGRAMS**





### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### **North America**

+1.800.753.9221

Option 1 – Customer Care

Option 2 - Technical Support

**Europe** 

Netherlands: +31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

nVent.com
TRACER