

# 1 HOLE TELECOM LUG



## **FEATURES**

Provides an efficient bolting surface for grounding and power applications

Electrolytic grade copper

For use with nVent ERICO Cadweld mold GLPCC001TC only

## **SPECIFICATIONS**


Material: Copper
Finish: Tinned


Table 1/2							
Catalog Number	Height (H)	Width (W)	Thickness (T)	Length (L)	A	Angle (a)	
B921CC14	7.93mm	15.88mm	3.18mm	22.23mm	9.5mm	90°	
B921CC38	7.93mm	15.88mm	3.18mm	22.23mm	9.5mm	90°	
B921CC516	7.93mm	15.88mm	3.18mm	22.23mm	9.5mm	90°	

Table 2/2					
Catalog Number	Hole Size (HS)	<b>Equivalent Conductor Size</b>			
B921CC14	7.14mm	50.39mm²			
B921CC38	10.32mm	50.39mm²			
B921CC516	8.73mm	50.39mm²			

For sizes not listed, contact us.

### **DIAGRAMS**





#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

