

ALARM BEACON SENSORS

Alarm Beacon sensors are accessories attached to nVent Enlogic iPDUs, which are designed to create a visible alarm notification for an alert condition (or other userdefined situation) in an effort to notify IT personnel quickly and efficiently. They provide information via Web UI, SNMP, CLI/SSH interfaces.

FEATURES

These devices produce visual alerts that direct users' attention to a designated area

The beacon is attached to an iPDU's sensor port 1 or port 2, and it flashes a red LED for 0.5 secs ON/0.5 secs OFF rhythmically until the issue is fixed or warnings are resolved

A standard RJ-45 connector may be used to extend the Alarm Beacon up to a distance of 30.5 meters

SPECIFICATIONS

Table 1/2								
Catalog Number	Product Type	Product Family	Width	Package Quantity	Height	Depth		
EA9101	Sensor	Enlogic	100mm	1	98mm	300mm		

Table 2/2								
Catalog Number	Removable Input Cable	Weight	Plug Type					
EA9101	No	0.5kg	RJ45					

ADDITIONAL PRODUCT DETAILS

Includes: (5) Cable Ties, (1) RJ45 Quick Disconnect Coupler, (5) Adhesive Backed Mounts, (1) 1.8m standard ethernet extension cable

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER