

DYNASPHERE AIR TERMINAL, MKIV



The economic and safety implications of lightning can be devastating. In general, the highest point of a facility is the most vulnerable to a direct lightning strike. Lightning rods or air terminals are needed to capture the strike to a preferred point and to safely conduct the energy to ground to minimize the risk.

The nVent ERICO Dynasphere air terminal provides a preferred point for lightning discharges which would otherwise strike and damage an unprotected structure and/or its contents. The primary function of an air terminal, or air termination system, is to capture the lightning strike to a preferred point, so that the discharge current can be directed via the downconductor(s) to the grounding system.

CERTIFICATIONS



FEATURES

Dynamic response to the approach of a lightning downleader


Non-radioactive technology

No external power required

Three replaceable terminals for specific elevation requirements

SPECIFICATIONS

| Table 1/1 | | | | | |
|-------------------|----------------|---------------|---------------------|------------|-------------|
| Catalog Number | Article Number | Temperature | Thread Size (TS) | Height (H) | Unit Weight |
| D/SMKIVSS | 702085 | -40 to 100 °C | 1/2" BSPP | 22 cm | 2.600 kg |



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.