


SOCKET STRIP, IEC C13





CERTIFICATIONS



FEATURES

230 V, 10 A

Horizontal and vertical mounting

Socket strips can be rotated through all four directions (in 90° increments) during installation

Socket strips with IEC 60320-C13 sockets

Connecting cable 2 m, open end with ferrules

In accordance with IEC 60320

Mounting height 1 U

SPECIFICATIONS

| Table 1/1 | | | | | | |
|-------------------|------------|-----------------|-------------|-------|-------|----------|
| Catalog Number | Voltage AC | Product Type | Socket Type | Depth | Color | Length |
| 60110-290 | 230 V | Socket Strip | IEC C13 | 44 mm | Grey | 438.5 mm |
| 60110-291 | 230 V | Socket Strip | IEC C13 | 44 mm | Grey | 438.5 mm |
| 60110-292 | 230 V | Socket Strip | IEC C13 | 44 mm | Grey | 608.5 mm |

ADDITIONAL PRODUCT DETAILS

Please order bracket for vertical mounting separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

nVent.com

2