

## SOCKET STRIP, UTE, MASTER-SLAVE, 6 SOCKETS, 19"



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with UTE outlets. When the master unit is switched on, the slave outputs are connected to the mains.

### CERTIFICATIONS



# EHL

### **FEATURES**

Connecting cable 2 m, with SCHUKO/UTE plug

Horizontal and vertical mounting

Socket strips can be rotated through all four directions (in 90° increments) during installation

230 V, 16 A

Mounting height 1 U

In accordance with NFC 61-303

When the master unit is switched on, the slave outputs are connected to the mains (switch threshold adjustable)

### SPECIFICATIONS

| Table 1/1         |            |                 |             |       |       |          |
|-------------------|------------|-----------------|-------------|-------|-------|----------|
| Catalog<br>Number | Voltage AC | Product<br>Type | Socket Type | Depth | Color | Length   |
| 60110-232         | 230 V      | Socket Strip    | UTE         | 44 mm | Grey  | 438.5 mm |

Please order bracket for vertical mounting separately.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.