

NVENT ERIFLEX FLEXBUS TRANSFORMER COVER IP2X FOR 1 CONDUCTOR PER PHASE



CERTIFICATIONS



FEATURES

Input/output for neutral/ground conductor

Resistance to solvent and hydrocarbon splashes


Installs quickly and easily

UV resistance

SPECIFICATIONS

Table 1/2							
Catalog Number	Article Number	Material	Length (L)	Working Temperature	Width (W)	Depth (D)	
FLEXCOVIP2XO NE	508160	Polyvinylchlorid e	465mm	-40 to 140°C	182mm	126mm	

Table 2/2					
Catalog Number	Article Number	Unit Weight			
FLEXCOVIP2XONE	508160	0.53kg			



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.