

UNIVERSAL TRANSIENT BARRIER, DUAL PAIR



CERTIFICATIONS



FEATURES

Compact design universal transient barrier provides protection of low-voltage circuits and transducers

Separate plug and base design allows hot swappable module replacement

Multi-stage protection and fine over-voltage protection helps ensure lowest residual surge voltages reach sensitive equipment

Common-mode and differential-mode protection protects against both possible surge conditions

Surge rating to 20 kA 8/20 μs is ideal for exposed wiring

Allows for protection of 25 analog signals or 50 digital signals per linear foot (0,3 m) of DIN rail space


SPECIFICATIONS

| Table 1/4 | | | | | | | |
|-------------------|-------------------|-----------------------------------|--|--------------------|---|----------------------------|--|
| Catalog Number | Article Number | Nominal System Voltage (Un) | Max Continuous Operating Voltage (Uc) | Loop Resistance | Max Discharge Current (Imax), L+L- PE | Rated Load Current (IL) | |
| UTB30DP | 702888 | 10 - 21 VAC, 15 - 30 VDC | 23 VAC, 33 VDC | 0.6 Ω | 20 kA 8/20 µs | 800 mA | |

| | | Table 2/4 | | | | | |
|-------------------|-------------------|-----------|---|---|-------------------------|--------------|--|
| Catalog Number | Article Number | Frequency | Technology | Voltage Protection Level (Up), L-L | Protection Modes | Temperature | |
| UTB30DP | 702888 | 2 MHz | Gas Discharge Tube (GDT), Metal Oxide Varistor (MOV), Silicon Avalanche Diode (SAD) | 44 V @ 3 kA | Common, Differential | -20 to 65 °C | |

| Table 3/4 | | | | | | | | | | |
|------------------------|--------------|----------|--------------------------|------------|-------------------------|--------------------------|-------------------|------------|-----------------------|-----------|
| Catalog Number | Artic Num | | Mounting | | Connection, Stranded | | nclosure ating | Height (H) | | Width (W) |
| UTB30DP | 70288 | 88 | 35 mm top ha DIN rail | it | 1 – 4 mm² | IP | 20, NEMA®-1 | 90 mm | | 12 mm |
| Table 4/4 | | | | | | | | | | |
| Catalog Number Article | | Number U | | nit Weight | | Certification Details | | | Replacement Module | |
| UTB30DP 702888 | | | 0.0 |)90 kg | | UL® 497B | | UTB30DPM | | |

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.

3