

NVENT CADDY CAT 425 ADJUSTABLE CABLE SUPPORT WITH BC200 BEAM CLAMP



CERTIFICATIONS





FEATURES

Easy installation to beam flanges

Rotates 360 degrees to support various directional runs of cable

Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic

Simple unlocking and locking of bar allows for additional cables to be added easily after installation

Adjustable strap allows for multiple support sizes to reduce inventory

Cost effective alternative to expensive cable tray

cULus® Listed and complies with NEC® and TIA requirements for structured cabling systems


Suitable for air handling spaces (plenum)

SPECIFICATIONS

Table 1/2										
Catalog Number	Article Number	Cable Capacity, Cat 6A	Cable Capacity, Cat 5e	Cable Capacity, Cat 6	Flange Thickness (FT)	Torque (TQ)				
CAT425BC200	181460	210	425	325	3.2 – 12.7mm	3N·m				

Table 2/2									
Catalog Number	Article Number	Diameter (Ø)	Area	Static Load (F)	Material	Finish			
CAT425BC200	181460	100mm, 150mm	13181mm²	450N	Steel, Polyethylene	Electrogalvanize d			

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



2