

SOCKET STRIP, SWISS



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with Swiss outlets.

CERTIFICATIONS



FEATURES

Socket strips can be rotated through all four directions (in 90° increments) during installation

230 V, 10 A

In accordance with SEV.IEC 60884

Connecting cable 2 m with Swiss version plug

Socket strips Swiss version

Installation height 1 U

Horizontal or vertical mounting

SPECIFICATIONS

| Table 1/2 | | | | | | | | | |
|-------------------|-----------------|-------------|--------------------|---------------------|-------|------------|--|--|--|
| Catalog Number | Product Type | Socket Type | Socket Quantity | Switched Outlets | Color | Voltage AC | | | |
| 60110-453 | Socket Strip | Swiss | 10 | No | Grey | 230V | | | |
| 60110-454 | Socket Strip | Swiss | 9 | Yes | Grey | 230V | | | |

| Table 2/2 | | | | | | | | | |
|-------------------|---------|-------|----------|------------------------|---------------------|--|--|--|--|
| Catalog Number | Length | Depth | Finish | Material | Package Quantity | | | | |
| 60110-453 | 438.5mm | 44mm | Anodized | Aluminum, Polyamide | 1 | | | | |
| 60110-454 | 438.5mm | 44mm | Anodized | Aluminum, Polyamide | 1 | | | | |

ADDITIONAL PRODUCT DETAILS

Please order bracket for vertical mounting separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

nVent.com CADDY ERICO HOFFMAN **RAYCHEM SCHROFF**