

# SOCKET STRIP, SCHUKO, WITH WIELAND® INPUT



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack. The Wieland connector allows easy combination with different power input cords.

### **CERTIFICATIONS**



#### **FEATURES**

Installation height 1 U

Output via SCHUKO sockets

Input via Wieland® GST 18 plug

Socket strips can be rotated through all four directions (in 90° increments) during installation

Horizontal or vertical mounting

In accordance with DIN 57620

## **SPECIFICATIONS**

Table 1/2							
Catalog Number	Voltage AC	Product Type	Socket Type	Function	Depth	Color	
60110-343	230 V	Socket Strip	SCHUKO		44 mm	Grey	
60110-344	230 V	Socket Strip	SCHUKO		44 mm	Black	
60110-345	230 V	Socket Strip	SCHUKO		44 mm	Red	
60110-352	230 V	Socket Strip	SCHUKO	Overcurrent Protection	44 mm	Grey	

Catalog Number	Voltage AC	ProductType	Socket Type	Function	Depth	Color
60110-353	230 V	Socket Strip	SCHUKO	Overcurrent Protection	44 mm	Black
60110-354	230 V	Socket Strip	SCHUKO	Overcurrent Protection	44 mm	Red

Table 2/2				
Catalog Number	Length			
60110-343	438.5 mm			
60110-344	438.5 mm			
60110-345	438.5 mm			
60110-352	438.5 mm			
60110-353	438.5 mm			
60110-354	438.5 mm			

## **ADDITIONAL PRODUCT DETAILS**

Please order bracket for vertical mounting separately.

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: