


# HORIZONTAL RAILS THREADED INSERT, M2.5



The threaded insert is a metal strip with thread M2.5 and allows the fixing of front panels.

## **CERTIFICATIONS**



## **FEATURES**

The collar screws used for fixing partial-width front panels must be 12.3 mm long

Usable for all horizontal rails

## **SPECIFICATIONS**

| Table 1/2         |            |                     |                 |   |                 |          |  |  |
|-------------------|------------|---------------------|-----------------|---|-----------------|----------|--|--|
| Catalog<br>Number | Rack Width | Package<br>Quantity | Product<br>Type | Product<br>Family   | Works With      | Material |  |  |
| 34561-384         | 84 HP      | 1                   | Threaded Insert | EuropacPRO, RatiopacPRO, RatiopacPRO AIR, CompacPRO, PropacPRO, Inpac | Subracks, Cases | Steel    |  |  |

| Catalog<br>Number | Rack Width | Package<br>Quantity | ProductType     | Product<br>Family   | Works With      | Material |
|-------------------|------------|---------------------|-----------------|---|-----------------|----------|
| 34561-328         | 28 HP      | 1                   | Threaded Insert | EuropacPRO,<br>RatiopacPRO,<br>RatiopacPRO<br>AIR,<br>CompacPRO,<br>PropacPRO,<br>Inpac | Subracks, Cases | Steel    |
| 34561-342         | 42 HP      | 1                   | Threaded Insert | EuropacPRO,<br>RatiopacPRO,<br>RatiopacPRO<br>AIR,<br>CompacPRO,<br>PropacPRO,<br>Inpac | Subracks, Cases | Steel    |
| 34561-363         | 84 HP      | 1                   | Threaded Insert | EuropacPRO,<br>RatiopacPRO,<br>RatiopacPRO<br>AIR,<br>CompacPRO,<br>PropacPRO,<br>Inpac | Subracks, Cases | Steel    |

| Table 2/2      |           |  |  |  |
|----------------|-----------|--|--|--|
| Catalog Number | Length    |  |  |  |
| 34561-384      | 431.3 mm  |  |  |  |
| 34561-328      | 146.82 mm |  |  |  |
| 34561-342      | 217.94 mm |  |  |  |
| 34561-363      | 324.62 mm |  |  |  |

### ADDITIONAL PRODUCT DETAILS

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF** 

**TRACER** 

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.