

# NVENT CADDY PYRAMID RL ADJUSTABLE ROLLER SUPPORT



# **FEATURES**

Height-adjustable roller-based support designed specifically for rooftop applications
Height adjustability allows for effective navigation of pipe around obstructions
Polymeric rollers ensure corrosion free rotation
Foam bottom offers low abrasion interface for better roof membrane protection
Compatible with roof surfaces including single ply, bituminous, metal and spray foam
Ready to use out of the box, saving installation time and labor

Hot-dip galvanized and UV stabilized for long lasting performance


## **SPECIFICATIONS**

Static Load Safety Factor:	3:1
Finish:	Hot-Dip Galvanized
Material:	Polyethylene;Polypropylene;Steel
Temperature:	-45 to 65 °C

Table 1/2								
Catalog Number	Article Number	Pipe Size	NB/DN	Height (H)	Length (L)	Width (W)		
PRA3H12	360473	3" Max	80 Max	152 - 305 mm	317.5 mm	203 mm		
PRA6H16	360474	6" Max	150 Max	165 - 406 mm	483 mm	203 mm		

Table 2/2								
Catalog Number	Article Number	A	Surface Area	Unit Weight	Static Load (F)			
PRA3H12	360473	159 mm	59355mm²	2 kg	1112N			
PRA6H16	360474	260 mm	91613mm²	2 kg	2670N			

## DIAGRAMS



#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

#### Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

### APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.