

SOCKET STRIP, IEC, 3-PHASE



Modular, compact PDU with many function elements. Using a 1 U by 1 U aluminum chassis the PDU can easily be integrated in a rack with IEC C13 and C19 outlets with 3 phase input.

CERTIFICATIONS



FEATURES

Socket strips with IEC sockets in accordance with IEC 60320

Vertical mounting

Socket strips can be rotated through all four directions (in 90° increments) during installation

Connecting cable 2 m

Mounting height 1 U

SPECIFICATIONS

Table 1/2							
Catalog Number	Voltage AC	Height	Product Type	Socket Type	Depth	Color	
60110-283	400 V	44 mm	Socket Strip	IEC C13	44 mm	Grey, Black, Red	
60110-284	400 V	44 mm	Socket Strip	IEC C13, IEC C19	44 mm	Grey, Black, Red	
60110-285	400 V	44 mm	Socket Strip	IEC C13, IEC C19	44 mm	Grey, Black, Red	

Table 2/2				
Catalog Number	Length			
60110-283	947.5 mm			
60110-284	947.5 mm			
60110-285	1753 mm			

ADDITIONAL PRODUCT DETAILS

Please order bracket for vertical mounting separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.