

# INTELLIGENT IPDU, EN1337, 230 VAC, 1-PH, 32 A

# **CATALOG NUMBER**

# **EN1337**



Modular, compact intelligent PDU with inlet metering. Ultra-Low Profile Design

# **FEATURES**

Enlogic EN1xxx Intelligent Power Distribution Units monitors input power of the entire PDU, provides billing grade unit level monitoring

High Visibility Data Display and Interactive Graphic Display

Measure circuit breaker loads across redundant feeds to avoid accidental downtime

Enables smart load balancing for power efficiency and maximized capacity utilization

Gigabit Ethernet Interface and redundant Ethernet (10/100)

iPDU DC power redundancy solution for up to 64 PDU's

Toolless Hot-Swap Controller

Input voltage 230 VAC, 1-phase

C13, C19 outlets

# PRODUCT ATTRIBUTES

Product Type: Socket Strip

Socket Type: (36) C13; (6) C19

Socket Quantity: 42

Color: Black

Switched Outlets: No

Circuit Breaker: 16 A, 1-pole, Hy-Mag

Circuit Breaker Quantity: 2

Current Rating: 7.4A

Finish: Powder Coated

Height: 1750mm

Input Cable Length: 3m

Input Cable Location: Top Feed

Input Current: 32 A

Input Voltage: 200-240 VAC, 1 PH

Interrupt Rating: 5kAIC

Max Power Input: 7.44 kVA

Metering Type: Input

Nominal Voltage: 230V

On/Off Switch Included: No

Output Voltage: 230VAC

Package Quantity: 1

Plug Type: IEC 60309 332P6 (IP44)

Product Family: Enlogic

Rack Units: 0U

Removable Input Cable: No

Type: Intelligent PDU

# ADDITIONAL PRODUCT DETAILS

Please order bracket for vertical mounting separately.

# **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



their respective owners.