

## EUROPACPRO 19" SUBRACK KIT FOR DIN CONNECTOR, SLIDE RAIL, RETROFIT SHIELDING



Non-shielded subrack for Din Connector mounting EN 60603-2 , Subrack can be assembled on slide rails to support the subrack inside a cabinet.

### CERTIFICATIONS



### FEATURES

Subrack with side panel type F ("flexible"), 19" bracket with notch for slide rail assembly

Installed load up to 11 kg

Subrack can be used with slide rails

Horizontal rails, rear, for connector mounting (IEC 60603-2 / DIN 41612)

Threaded insert pre-fitted

### SPECIFICATIONS

Table 1/3

Catalog Number	For Mounting	Board Depth	EMC Gasket Type	EMC Shielding	Rack Width	Handle Included
24553-192	DIN Connector	160 mm, 220 mm	Stainless Steel	No	84 HP	No
24553-193	DIN Connector	160 mm, 220 mm, 280 mm	Stainless Steel	No	84 HP	No

Catalog Number	ForMounting	Board Depth	EMC Gasket Type	EMC Shielding	Rack Width	Handle Included
24553-194	DIN Connector	160 mm, 220 mm, 280 mm, 340 mm	Stainless Steel	No	84 HP	No
24553-492	DIN Connector	160 mm, 220 mm	Stainless Steel	No	84 HP	No
24553-493	DIN Connector	160 mm, 220 mm, 280 mm	Stainless Steel	No	84 HP	No
24553-494	DIN Connector	160 mm, 220 mm, 280 mm, 340 mm	Stainless Steel	No	84 HP	No

Table 2/3						
Catalog Number	Package Quantity	Product Type	Rack Height	Complies With	Mounting	Depth
24553-192	1	Subrack/Chassis	3 U	IEC 60297-3-103	Rack	235 mm
24553-193	1	Subrack/Chassis	3 U	IEC 60297-3-103	Rack	295 mm
24553-194	1	Subrack/Chassis	3 U	IEC 60297-3-103	Rack	355 mm
24553-492	1	Subrack/Chassis	6 U	IEC 60297-3-103	Rack	235 mm
24553-493	1	Subrack/Chassis	6 U	IEC 60297-3-103	Rack	295 mm
24553-494	1	Subrack/Chassis	6 U	IEC 60297-3-103	Rack	355 mm

Table 3/3	
Catalog Number	Static Load
24553-192	11 kgf
24553-193	11 kgf
24553-194	11 kgf
24553-492	11 kgf
24553-493	11 kgf
24553-494	11 kgf

## ADDITIONAL PRODUCT DETAILS

Individual configuration: broad range of variants in height, width and depth; guide rails for a wide variety of applications; interior options; accessories and mounting material.

## **WARNING**

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**