

NVENT CADDY CAT HP J-HOOK WITH MULTI-FUNCTION CLIP



CERTIFICATIONS

FEATURES

Quick attachment to threaded rod or wire

Fully adjustable and easy to relocate to accommodate changes once installed

Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic

Provides superior fill capacity and load rating over most other non-continuous cable support alternatives

Rounded edges on J-Hooks provide proper bend radius support for high performance data cables

Cost effective alternative to expensive cable tray

Complies with EN 50174-2

Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569

Increased capability and application options by combining 4Z and 6Z products into one enhanced and efficient offering

Improved multi-function clip allows for optimized inventory while reducing job site scheduling risks associated with multiple SKUs

SPECIFICATIONS

Finish:Pregalvanized; nVent CADDY ArmourMaterial:Steel; Spring Steel

Table 1/2								
Catalog Number	Article Number	Cable Capacity, Cat 6A	Cable Capacity, Cat 5e	Cable Capacity, Cat 6	Wire Size	Rod Size (RS)		
CAT16HP4Z34	181217	10	20	15	3.9 – 4.8mm	4, 6, 8, 10		
CAT21HP4Z34	181258	25	50	40	3.9 – 4.8mm	4, 6, 8, 10		
CAT32HP4Z34	181218	35	90	60	3.9 – 4.8mm	4, 6, 8, 10		

Table 2/2								
Catalog Number	Article Number	Diameter (Ø)	Area	Static Load (F)				
CAT16HP4Z34	181217	25mm	690mm²	130N				
CAT21HP4Z34	181258	33.3mm	1174mm ²	130N				
CAT32HP4Z34	181218	50mm	2561mm²	130N				

ADDITIONAL PRODUCT DETAILS

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.

Cable capacity is calculated based on a 70% fill rate.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.

3