

NVENT ERICO SYSTEM 3000 INTERCEPTOR



CERTIFICATIONS



FEATURES

Dynamic response to the approach of a lightning downleader

Designed for lower height installations


Non-radioactive technology

No external power required

SPECIFICATIONS

Table 1/2									
Catalog Number	Article Number	Material	Temperature	Installation Height (H)	Diameter 1 (Ø1)	Diameter 2 (Ø2)			
INTMKIVSS	702089	Stainless Steel 316 (EN 1.4401)	-40 to 100°C	20m max	101.6mm	26.15mm			

Table 2/2								
Catalog Number	Article Number	Thread Size (TS)	Height (H)	Unit Weight				
INTMKIVSS	702089	1/2" BSPP	348mm	2.06kg				



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.