

# FRONT PANEL, UNSHIELDED, WITH FASTENER PIN



Front panel with GND/earthing connection. The grounding can be done with a cable which fits to the fastener pin on the rear side of the panel.

### **CERTIFICATIONS**



# **FEATURES**

Enable grounding of the front area (protection class 1)

# **SPECIFICATIONS**

Table 1/3						
Catalog Number	Treated Edges	Front Finish	Rear Finish	EMC Shielding	Rack Width	Package Quantity
20119-159	No	Anodized	Conductive	No	7 HP	1
20119-160	No	Anodized	Conductive	No	14 HP	1
20119-161	No	Anodized	Conductive	No	21 HP	1
20119-162	No	Anodized	Conductive	No	28 HP	1
20119-163	No	Anodized	Anodized	No	42 HP	1

Table 2/3						
Catalog Number	Height	Product Type	Туре	Rack Height	Width	Complies With

20119-159	128.4 mm	Front Panel	Front Panel without Handle	3 U	35.2 mm	IEC 60297-3- 101, IEEE 1101.1/10
20119-160	128.4 mm	Front Panel	Front Panel without Handle	3 U	70.8 mm	IEC 60297-3- 101, IEEE 1101.1/10
20119-161	128.4 mm	Front Panel	Front Panel without Handle	3 U	106.3 mm	IEC 60297-3- 101, IEEE 1101.1/10
20119-162	128.4 mm	Front Panel	Front Panel without Handle	3 U	141.9 mm	IEC 60297-3- 101, IEEE 1101.1/10
20119-163	128.4 mm	Front Panel	Front Panel without Handle	3 U	213 mm	IEC 60297-3- 101, IEEE 1101.1/10

Table 3/3					
Catalog Number	Mounting	Material			
20119-159	Screw-on Front	Aluminum			
20119-160	Screw-on Front	Aluminum			
20119-161	Screw-on Front	Aluminum			
20119-162	Screw-on Front	Aluminum			
20119-163	Screw-on Front	Aluminum			

#### ADDITIONAL PRODUCT DETAILS

Please order fixing material (sleeves, collar screws) separately.

Delivery is in standard pack multiples. Pricing is per individual item.

Please take into consideration that deliveries may be carried out in the stated SPQs (SPQ, e.g. 5 pieces, 10 pieces, 50 pieces, etc.). Differing order quantities (e.g. 2 pieces) may be changed to the next possible delivery quantity = Standard Pack Quantity.

# **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF** 

**TRACER** 

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.