


## CABLE TO REBAR, RD, 25 MM, #8, 25M, 19/#9 COPPERWELD

### CATALOG NUMBER

**RDH569F**



nVent ERICO Cadweld graphite molds are designed and engineered for thousands of connection styles and conductor combinations.

### FEATURES

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

### PRODUCT ATTRIBUTES

Schweißtiegel Familie: RD Mold Family

Rebar Size, Metrisch: 25mm

Bewehrungsstrahlgröße, US: #8

Rebar Size, Kanada: 25M

Querschnitt Elektrischer Leiter: 19/#9 Copperweld

elektrischer Leiter Außendurchmesser, nominal: 14.53mm

Mold Split: Vertikal

Geteilter Schmelztiegel: Nein

Verschleißplatten: Nein

Nur Schweißtiegel: Nein

Schweißmaterial: 150 oder 150PLUSF20, separat erhältlich

Batting/Packing Material: B144C, Sold Separately

Preisschlüssel: H

Benutzerfreundlichkeit: Bevorzugt

## ADDITIONAL PRODUCT DETAILS

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, 150 becomes XL150).


A gap between conductors may be required. See mold tag for more information.

Rebar material characteristics and location of weld must be considered when selecting connections to rebar.

XX-X-XX-XX-L-M-W		
XX	Mold Family	
X	Price Key	
XX	Rebar Code	
XX	Conductor Code	
L*	Split Crucible	Crucible section is split on molds designed with horizontal opening for easier cleaning
M*	Mold Only	
W*	Wear Plates	Reduce mechanical abrasion of molds at cable entry points

\* Empty if none

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**