

EXPRESS RACK TOP BAFFLE, 10.90X23.60X22.50, BLACK, POLYCARBONATE ABS

CATALOG NUMBER

UACTB6A



The Rack Top Baffles are suitable for most standard width cabinets with solid, perforated or semi-solid steel tops. The baffles will not work with aluminum framed cabinets or open framed racks.

FEATURES

Allows additional natural light into aisle

The Rack Top Baffles require a minimum of 1 inch (25 mm) unobstructed depth across the entire front edge of the cabinet for secure attachment

Additionally, the two attachment fixtures on each baffle require a 1.50 x 5.50 inch (38 x 140 mm) unobstructed area on the top of the cabinet

These attachment mounts allow a high degree of flexibility across the top of the cabinet to work around obstructions

Prevents hot exhaust air from wrapping over the tops of racks

Attaches to top of rack magnetically

Angular baffle designed for cold aisle application

Vertical baffle is designed for hot aisle application

Reconfigurable design allows angular or vertical configuration

Tool-less Ceiling Panels are easy to install and remove for cleaning and provide above-the-cabinet access to cables, equipment and systems

Clear, transparent door and roof panels provide maximum light to aisleway

Express containment system includes magnetic mounting for quick-install

Express containment top baffles include both hot and cold aisle configurations

PRODUCT ATTRIBUTES

Article Number: 38607

Width: 23.6inDepth: 22.5inMaterial: PVCFinish: Powder CoatedColor: Jet BlackColor Code: RAL 9005Weight: 2lb	Height: 10.9in		
Material: PVC Finish: Powder Coated Color: Jet Black Color Code: RAL 9005	Width: 23.6in		
Finish: Powder Coated Color: Jet Black Color Code: RAL 9005	Depth: 22.5in		
Color: Jet Black Color Code: RAL 9005	Material: PVC		
Color Code: RAL 9005	Finish: Powder Coated		
	Color: Jet Black		
Weight: 2lb	Color Code: RAL 9005		
	Weight: 2lb		

ADDITIONAL PRODUCT DETAILS

Custom sizes are available

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.