

VARISTAR CP SWING FRAME FOR 800 MM WIDTH

The 19" swing frame allows the installation of sub-racks while simultaneously making wiring at the rear accessible.

Varistar CP swing frame comes with 150 KG load capacity, 120° / 160° movement and flexible pivot point.

FEATURES

For full height or partial-height mounting

Pivot point can be selected right or left

Can accommodate 19" chassis and 19" subracks

120° / 160° hinge, square locks including 2 keys

Load-carrying capacity 150 kg

SPECIFICATIONS

Table 1/2

Catalog Number	Product Type	Product Family	Rack Height	Color	Material	Color Code
21630-669	Cabinet/Rack Frame	Varistar CP	24 U	Black Grey	Steel	RAL 7021
21630-680	Cabinet/Rack Frame	Varistar CP	24 U	Black Grey	Steel	RAL 7021
21630-671	Cabinet/Rack Frame	Varistar CP	29 U	Black Grey	Steel	RAL 7021
21630-681	Cabinet/Rack Frame	Varistar CP	29 U	Black Grey	Steel	RAL 7021
21630-673	Cabinet/Rack Frame	Varistar CP	33 U	Black Grey	Steel	RAL 7021
21630-682	Cabinet/Rack Frame	Varistar CP	33 U	Black Grey	Steel	RAL 7021
21630-675	Cabinet/Rack Frame	Varistar CP	38 U	Black Grey	Steel	RAL 7021
21630-683	Cabinet/Rack Frame	Varistar CP	38 U	Black Grey	Steel	RAL 7021
21630-677	Cabinet/Rack Frame	Varistar CP	42 U	Black Grey	Steel	RAL 7021

Catalog Number	ProductType	Product Family	Rack Height	Color	Material	Color Code
21630-684	Cabinet/Rack Frame	Varistar CP	42 U	Black Grey	Steel	RAL 7021
21630-679	Cabinet/Rack Frame	Varistar CP	47 U	Black Grey	Steel	RAL 7021
21630-685	Cabinet/Rack Frame	Varistar CP	47 U	Black Grey	Steel	RAL 7021

Table 2/2

Catalog Number	Protection Rating
21630-669	IP20
21630-680	IP20
21630-671	IP20
21630-681	IP20
21630-673	IP20
21630-682	IP20
21630-675	IP20
21630-683	IP20
21630-677	IP20
21630-684	IP20
21630-679	IP20
21630-685	IP20

ADDITIONAL PRODUCT DETAILS

By aid of depth members 19" swing frames can be assembled directly on the cabinet frame or in depth-adjustable increments of 50 mm.

Please purchase the grounding kit separately.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER