

## CABLE TO WEB OF RAIL MOLD ONLY, SIGNAL



## **FEATURES**

Replacement mold designed for the installation of track circuits and jumper bonds to the neutral axis

## **SPECIFICATIONS**

Rail Type: 85 lb to 141 lb T-Rail Sections

Material: Graphite

Table 1/2							
Catalog Number	Bond Terminal Style	Handle Clamp	Conductor Outer Diameter, Nominal	Welder Style	Welding Material	Orientation	
SBB200CLH	1" Tab		4.76mm	TB5, T21	SB25, Sold Separately	Left Hand	
SBB200CRH	1" Tab		4.76mm	TB5, T21	SB25, Sold Separately	Right Hand	
SBW3150BLH	1" Tab	C105B, Sold Separately	4.76mm	TB5	SB25 or SB25PLUSF80, Sold Separately	Left Hand	
SBW3150BRH	1" Tab	C105B, Sold Separately	4.76mm	TB5	SB25 or SB25PLUSF80, Sold Separately	Right Hand	
SBB200YLH	1" Tab	C105B, Sold Separately	5.18mm	T21, TB5	SB25 or SB25PLUSF80, Sold Separately	Left Hand	

Catalog Number	Bond Terminal Style	Handle Clamp	Conductor Outer Diameter, Nominal	Welder Style	Welding Material	Orientation
SBB200YRH	1" Tab	C105B, Sold Separately	5.18mm	T21, TB5	SB25 or SB25PLUSF80, Sold Separately	Right Hand
SBB200XRH	1" Tab		6.6mm	TB5, T21	SB32, Sold Separately	Right Hand
SBB200PLH	1" Tab		7.75mm	TB5, T21	SB32, Sold Separately	Left Hand
SBB200PRH	1" Tab		7.75mm	TB5, T21	SB32, Sold Separately	Right Hand
SBWW6LH	Field-made	C105B, Sold Separately	8mm	T21	SB32 or SB25PLUSF80, Sold Separately	Left Hand
SBWW6RH	Field-made	C105B, Sold Separately	8mm	T21	SB32 or SB25PLUSF80, Sold Separately	Right Hand

Table 2/2				
Catalog Number	Conductor Size			
SBB200CLH	3/16" Bondstrand			
SBB200CRH	3/16" Bondstrand			
SBW3150BLH	3/16" Bondstrand			
SBW3150BRH	3/16" Bondstrand			
SBB200YLH	16 mm² Concentric			
SBB200YRH	16 mm² Concentric			
SBB200XRH	25 mm² Stranded			
SBB200PLH	35 mm² Stranded			
SBB200PRH	35 mm² Stranded			
SBWW6LH	50 mm² Solid			
SBWW6RH	50 mm² Solid			

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF** 

**TRACER** 

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.