

CABLE TO REBAR, RD, 22 MM, #7, 3/0 CONCENTRIC, MOLD ONLY

目录编号

RDH552LM



nVent ERICO Cadweld graphite molds are designed and engineered for thousands of connection styles and conductor combinations.

CERTIFICATIONS



功能

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

产品属性

模具系列: RD Mold Family

钢筋尺寸,metric: 22mm

钢筋尺寸,美国: #7

导体尺寸: 3/0 Concentric			
导体公称外径: 11.94mm			
Mold Split: Vertical			
分体坩埚: No			
耐磨板: No			
仅模具: Yes			
焊药: 150 or 150PLUSF20, Sold Separately			
框架: B227AX, Sold Separately			
Batting/Packing Material: B144C, Sold Separately			
定价关键: H			
易用: Preferred			

ADDITIONAL PRODUCT DETAILS

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, 150 becomes XL150).

A gap between conductors may be required. See mold tag for more information.

Rebar material characteristics and location of weld must be considered when selecting connections to rebar.

XX-X-XX-L-M-W			
ХХ	Mold Family		
х	Price Key		
ХХ	Rebar Code		
ХХ	Conductor Code		
L*	Split Crucible	Crucible section is split on molds designed with horizontal opening for easier cleaning	
М*	Mold Only		
W*	Wear Plates	Reduce mechanical abrasion of molds at cable entry points	

* Empty if none



警告

应仅根据 nVent 的产品说明书与培训材料安装并使用 nVent 的产品。可访问 www.nvent.com 获取说明书,或者向您的 nVent 客服代表索取。错误安装、使用不当、滥用或未能完全遵守 nVent 的说明与警告,可能会造成产品故障、财产损失、严重的人身伤害及死亡和/或使得保修服务无效。



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

 \odot 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks 3 are the property of their respective owners.

nVent reserves the right to change specifications without notice.